

IN THE CLAIMS:

Please cancel claims 16-23 without prejudice or disclaimer.

1. (Previously Presented) A printing apparatus including transporting means for transporting a print medium relative to printing means for printing an image on a print medium, the apparatus comprising:

a carriage for supporting said printing means and reciprocating said printing means in a direction crossing a direction in which the print medium is transported; and

control means for controlling said printing apparatus so that said printing apparatus performs a transportation by said transporting means and printing by said printing means in sequence, and so that said carriage moves to vibrate said transporting means without performing a printing after said transporting means completes a transportation and before said printing means starts a printing.

2. (Original) A printing apparatus according to claim 1, wherein said transporting means comprises a movable member installed so as to move or stop relative to a travel path for the print medium, and said movable member contracts, while moving, with the print medium in said travel path to transfer the print medium, and is held, while stopped, at a predetermined stabilized position normally.

3. (Original) A printing apparatus according to claim 1, wherein said transporting means comprises a pair of rollers installed in the travel path for the print medium

and opposite each other, roller urging means for urging said pair of rollers so that the rollers sandwich the print medium therebetween, and driving means for rotationally driving at least one of said pair of rollers.

4. (Previously Presented) A printing apparatus according to claim 3, wherein said pair of rollers comprises a transportation roller located upstream of the printing means in a transporting direction thereof and driven by a predetermined driving means, and a pinch roller that rotates in connection with the transportation roller.

Claim 5 (Cancelled).

6. (Previously Presented) A printing apparatus according to claim 1, wherein said carriage moves to vibrate the transporting means by performing at least one reciprocation.

7. (Previously Presented) A printing apparatus according to claim 1, further comprising a pressure plate that supports the print medium, a sheet feeding roller that feeds print medium supported on said pressure plate, a spring for pressuring a print medium supported by said pressure plate onto said feeding roller, and

releasing means for placing a space between said pressure plate and said sheet feeding roller.

8. (Previously Presented) A printing apparatus according to claim 7, wherein said pressure plate is movable in forward and backward direction relative to said sheet feeding roller, wherein the forward and backward movement is carried out in connection with a sheet feeding operation performed by said sheet feeding roller, and while said pressure releasing means is performing a pressing or releasing operation, the driving of said sheet feeding roller is interrupted.

9. (Previously Presented) A printing apparatus according to claim 4, further comprising a pinch roller holder that rotatably supports said pinch roller.

10. (Previously Presented) A printing apparatus according to claim 4, wherein said carriage moves to vibrate said transporting means after at least a back end of the print medium has passed through an abutted portion between said transportation roller and said pinch roller.

11. (Previously Presented) A printing apparatus according to claim 4, further comprising detection means for detecting a position at which said transportation roller is stopped, and if it is detected that said transportation roller stopped position is deviate from a desired one after said carriage has moved to vibrate the transporting means, then said transportation roller stopped position is corrected before a print head performs a printing operation.

12. (Previously Presented) A printing apparatus according to claim 4, further comprising detection means for detecting a position at which said transportation roller is stopped, and if it is detected that said transportation roller stopped position is deviate from a desired on after said carriage has moved to vibrate the transporting means, then printing is carried out by shifting an operative portion of the printing means in the transporting direction depending on the amount of the positional deviate.

13. (Original) A printing apparatus according to claim 11, wherein said detection means comprises a signal generator that generates pulse signals the number of which corresponds to rotation of said transportation roller, and counting means for counting the number of signals from the signal generator.

14. (Original) A printing apparatus according to claim 12, wherein said detection means comprises a signal generator that generates pulse signals the number of which corresponds to rotation of said transportation roller, and counting means for counting the number of signals from the signal generator.

15. (Original) A printing apparatus according to claim 1, wherein said printing means uses thermal energy to generate bubbles in ink so that energy generated by the bubbles causes the ink to be ejected.

Claims 16-23. (Cancelled)